

ARMOURING MACHINES

Engineered Armouring Solutions

Calmec's Armouring Machines offer the most advanced technology for producing round armoured cables, flat down-well pump cables (ESP), and interlocked conduit. Built for speed, durability, and precision.

GENERAL OVERVIEW

- Calmec's Single Strip (CT1) and Patented Dual Strip (CT2) Production Lines offer:
- True triple drive system - AC vector or servo motor controlled
- Adjustable tooling head angles; balanced with fixed positions
- Multiple machine sizes; 1¼", 2", 4" and 5"
- Aluminum, steel, stainless steel and Monel materials
- 3/8" to 3/4" wide strip, depending on machine size, with maximum pad weights up to 1,500 lbs.
- For traverse wound strip coils; 6", 9" and 12" nominal widths
- Electric strip tensioning system with automatic self-adjustment - no wear items
- Off-line tooling setups for reduced downtime
- Pneumatic coil chucking
- Colour touch screen process setup with product recipes
- Automatic mist lubrication regulation with recirculation



KEY FEATURES

- Head assembly designed for positive and fast tool changeover, with off-line setup capability
- Multiple fixed head angles with balanced positions provide optimum positive placement and higher running speeds at all head angles
- Hardened tooling throughout for longer wear
- Menu driven colour touch screen for full product range, with recipe specific parameters & tooling requirements, display of system parameters, and maintenance screens
- LED lighting throughout
- Rotational Strip Storage Stands, Coil Rotators, and Coil Transfer stands also available



Calmec Precision Limited
1400 Bonhill Road
Mississauga, ON Canada
011-1-905-677-7976
sales@calmec.com
www.calmec.com



ARMOURING MACHINES

Engineered Armouring Solutions

MULTIPLE MOTOR DRIVE SYSTEM

- Four independent AC vector or optional servo motors; one for the main spindle, for the strip feed, for strip tensioning, and for the Cater
- Puller or capstan - drives combined on a common DC bus
- True full motor system, no differential or gear box required; drives digitally synchronized
- Multiple drives eliminate the mechanical variator, PIV, or differential and all the associated mechanical maintenance issues
- Drives can also operate independently for set-up purposes, meaning the strip feed rolls can be run while the tooling head remains stationary; a safer and efficient tooling setup

SPECIFICATIONS

SINGLE STRIP (CT1)

MACHINE MODEL	NOMINAL SIZE	MAX. MACHINE SPEED	MAX. LINE SPEED	STRIP WIDTH RANGE
CT1 - 32	1 1/4" (32MM)	1200 RPM	35 FEET/ MINUTE	3/8" - 1/2"
CT1 - 50	2" (50MM)	1200 RPM	35 FEET/ MINUTE	3/8" - 1/2"
CT1 - 100	4" (100MM)	1000 RPM	40 FEET/ MINUTE	1/2" - 3/4"
CT1 - 125	5" (125MM)	800 RPM	32 FEET/ MINUTE	1/2" - 3/4"

DUAL STRIP (CT2)

MACHINE MODEL	MAX. SIZE	MAX. MACHINE SPEED	MAX. LINE SPEED	STRIP WIDTH RANGE
CT2 - 32	1 1/4" (32MM)	1200 RPM	70 FEET/ MINUTE	3/8" - 1/2"
CT2 - 50	2" (50MM)	1000 RPM	70 FEET/ MINUTE	3/8" - 3/4"
CT2 - 125	5" (125MM)	800 RPM	64 FEET/ MINUTE	1/2" - 3/4"

POT STYLE

MACHINE MODEL	NOMINAL SIZE	MAX. MACHINE SPEED	MAX. LINE SPEED	STRIP WIDTH RANGE
CT1P - 40	1 1/2" (40MM)	800 RPM	25 FEET/ MINUTE	3/8" - 3/4"

All machines accept metallic coils .010" -.040" strip thickness. Head angles are dependent on product size and reach 11 degrees on CT1 single strip machines, and 30 degrees on CT2 dual strip machine. Adjustable head angles optimize strip flow with minimum strip deformation.



Calmec Precision Limited
1400 Bonhill Road
Mississauga, ON Canada
011-1-905-677-7976
sales@calmec.com
www.calmec.com

